

Specifications

Construction: High Density
Fiberboard

Edge Type: V-Groove

Thickness: 12.3mm

Length: 48"

Width: 7-5/8"

Coverage per Carton: 25.5 ft²

Pieces per Carton: 10

Weight per Carton: 55 lbs.

Installation Method: Floating

Recommended Usage: Residential

Underlayment Required: Yes



This product is protected by a 25
year residential warranty



Abrasion Class 3 Rating works well in
all areas of the home and can
withstand normal household traffic




This floor is compliant with Phase 2
emissions standards of the California
Air Resources Board. Formaldehyde
is less than 0.05%

We have carefully crafted this beautiful floor to closely resemble the
reclaimed wood look that has become wildly popular across the country.
From warm tones to bold variation-the Forever collection has it all.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


Recommended Underlayment



2mm or
3mm Blue




2mm or
3mm Silver



EVA



XPE



Felt



Rubber



¼ Cork



½ Cork

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding