

Specifications

Construction: High Density Fiberboard

Edge Type: V-Groove/Pressed

Thickness: 12.3mm

Length: 48"

Width: 6-1/2"

Coverage per Carton: 25.63/21.67 ft²

Pieces per Carton: 10

Weight per Carton: 56/50 lbs.

Installation Method: Floating

Recommended Usage: Residential & Light Commercial

Underlayment Required: Yes



This product is protected by a 50 year residential/5 year commercial warranty



Abrasion Class 4 Rating works well in all areas of the home and can withstand moderate commercial traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board. Formaldehyde is less than 0.05%

The Quality Collection delivers an array of striking colors enhanced by an attractive finish. Eye-catching variations make this floor incredibly unique.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance

Recommended Underlayment



2mm or 3mm Blue



2mm or 3mm Silver



EVA



XPE



Felt



Rubber



1/4 Cork



1/2 Cork

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding