

Specifications

Construction: High Density Fiberboard

Edge Type: V-Groove

Thickness: 12.3mm

Length: Random 24", 48", 72"

Width: 7-1/2"

Coverage per Carton: 22.44 ft²

Pieces per Carton: 9

Weight per Carton: 47 lbs.

Installation Method: Floating

Recommended Usage: Residential & Light Commercial

Underlayment Required: Yes



This product is protected by a 50 year residential/5 year commercial warranty



Abrasion Class 4 Rating works well in all areas of the home and can withstand moderate commercial traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board. Formaldehyde is less than 0.05%

The Timeless Collection is a classic for the modern world. The unique style of this floor allows you to mix it with traditional or contemporary décor and it is truly one of our most unique creations.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


Recommended Underlayment



2mm or 3mm Blue




2mm or 3mm Silver



EVA



XPE



Felt



Rubber



1/4 Cork



1/2 Cork

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding