

Specifications

Construction: Vinyl, PVC décor film, UV Coating

Edge Type: Square

Overall Thickness: 2mm

Wear Layer: 0.2mm (8mil)

Length: 48"

Width: 6-1/4"

Coverage per Carton: 41.47 ft²

Pieces per Carton: 20

Weight per Carton: 31 lbs.

Installation Method: Glue Down

Recommended Usage: Residential

Underlayment Required: No



This product is protected by a 10 year residential warranty



VOC Emissions for this product are excellent-below ½ acceptable CREL Levels



Impact Sound Transmission Rating for this floor is 7

The luxurious embossing of the Colonial Collection gives our vinyl planks the look of natural wood floors. Resistant to scratches, marks, and stains-vinyl is the perfect fit for homes with light to moderate foot traffic.

Features

- UV Resistant*
- Fade Resistant*
- Fire Resistant*
- Hypoallergenic*
- Scratch Resistant*
- Non Toxic*
- Slip Resistant*
- Mildew Resistant*
- Stain Resistant*
- Easy Maintenance*

Recommended Adhesive

Duvall K-PSA Pressure Sensitive Adhesive. Solvent Free formula. "Zero" calculated VOC. Resists Plasticizer Migration. Low Odor.

Technical Data

Squareness	ASTM F2055-10	≤ 0.01"
Fire	ASTM E84	75 or less
	ASTM E648	Class I
Smoke	ASTM E662	Pass
Residual Indentation	ASTM F1914	≤ 8%
Static Load Limit	ASTM F970	1500 psi
Flexibility	ASTM F137	Pass
Hardness-Durometer	Shore A	90 ± 5
Dimensional Stability	ASTM F2199	Pass
Slip Resistance	ASTM 1028 (Exceeds ADA/OSHA req.)	
Color Fastness	ISO 105-B02	≥ Grade 6
Radiant Heat Suitability	Up to 85 degrees Fahrenheit	
Chair Castor Resistance	Phillips Roll Chair 5 @ 25,000 cycles	