

Specifications

Construction: Vinyl, PVC décor film, UV Coating

Edge Type: Square

Overall Thickness: 2mm

Wear Layer: 0.3mm (12mil)

Length: 48"

Width: 6-1/4"

Coverage per Carton: 41.47 ft²

Pieces per Carton: 20

Weight per Carton: 33 lbs.

Installation Method: Glue Down

Recommended Usage: Residential & Light Commercial

Underlayment Required: No



This product is protected by a 15 year residential/5 year light commercial warranty



This floor is easy to maintain



This product is waterproof and won't be affected by household spills

The Hacienda Collection is one that provides a sense of charm in a grand array of colors for your home. You will have peace of mind when it comes to spills and household traffic as this vinyl floor comes with a commercial warranty.

Features

- ✓ *UV Resistant*
- ✓ *Fade Resistant*
- ✓ *Fire Resistant*
- ✓ *Hypoallergenic*
- ✓ *Scratch Resistant*
- ✓ *Non Toxic*
- ✓ *Slip Resistant*
- ✓ *Mildew Resistant*
- ✓ *Stain Resistant*
- ✓ *Easy Maintenance*

Recommended Adhesive

Duvall K-PSA Pressure Sensitive Adhesive. Solvent Free formula. "Zero" calculated VOC. Resists Plasticizer Migration. Low Odor.

Technical Data

Manufacturing standard	EN 649	pass
Total thickness	EN 428	2.0mm
Thickness of wear layer	EN 429	0.3mm
Peeling strength of layers	EN 431	Pass
Size tile (L x W)	EN 427	157 x 1227mm
Sound, impact, reduction	EN ISO 717-2	>4.8 dB
Fire resistance	EN 13501-1	Bfl-S1
Dimension stability after exposure to heat	EN 434	< 0,10%
Colour fastness to light	ISO 105 B02	grade > 6
Static indentation		0.02mm
Flexibility	EN 435	pass
Abrasion resistance	EN 660	class T
Castor chair resistance	EN 425	pass
Slip resistance	EN 13893/DIN 51131	>= 0,3/ R10
Anti-sliding properties	class DS	μ = 0,59
Usage category	EN 685	23/31
Resistance to chemicals		pass
Light fastness	ISO 105-B02-3	> 6
Surface treatment		Semi-matt