

Specifications

Construction: Vinyl, Composite Core,
UV Coating + PVC Décor Film
Edge Type: Micro Beveled
Overall Thickness: 7mm
Wear Layer: 0.5mm (20mil)
Nominal Length: 24"
Nominal Width: 12"
Coverage per Carton: 20.03 ft²
Pieces per Carton: 10
Weight per Carton: 34 lbs.
Installation Method: Floating
Recommended Usage: Residential &
Light Commercial
Underlayment Required: Yes



This product is protected by a 50
year residential/10 year light
commercial warranty



This floor is waterproof and won't be
affected by household spills

Features

- | | |
|---|--|
| <input checked="" type="checkbox"/> UV Resistant | <input checked="" type="checkbox"/> Fade Resistant |
| <input checked="" type="checkbox"/> Fire Resistant | <input checked="" type="checkbox"/> Hypoallergenic |
| <input checked="" type="checkbox"/> Scratch Resistant | <input checked="" type="checkbox"/> Non Toxic |
| <input checked="" type="checkbox"/> Slip Resistant | <input checked="" type="checkbox"/> Mildew Resistant |
| <input checked="" type="checkbox"/> Stain Resistant | <input checked="" type="checkbox"/> Easy Maintenance |

Recommended Underlayment

- **VersaPro** 1mm Black /Green Underlayment
- **VersaPro PLUS** 1.5mm Black / Green Underlayment
- **WPCZS** 1.5mm Zero Slip High Density Black / Blue Underlayment
- **RUBBER Enhanced** 2mm Acoustical Silver / Green Underlayment

Certifications



GREENGUARD Certification ensures that a product has met some of the world's most rigorous and comprehensive standards for low emissions of volatile organic compounds (VOCs) into indoor air.



FloorScore® is the most recognized indoor air quality (IAQ) certification standard for hard surface flooring materials, adhesives, and underlayments.

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding

Product	Overall Thickness	7.0mm (No Pad) (2.0mmLvt+5.0wpc)		
Dimensions	Width and Length	305mmW x 610mmL		
Packaging (Per Carton)		10 Planks	20.03 Sq.Ft.	34 Lbs
Construction	Top Layers	High Definition Decor Film		
		Enhanced Polyurethane Coating		
		0.5mm Wear Layer		
	Core	5.0mm Limestone Composite: min. 45% stone, 0% wood,		
		100% Virgin Material		
	Density	1200kg/m³±10%		
	Pad	No pad		
Bevel	Bevel			
Installation	Floating Glueless			
Under Floor Heating	Approved - See installation manual for details.			
Warranty	50 Year Residential/10 Years Light Commercial			
Test Data				
Static Load	ASTM F970	500PSI		
Heat Exposure Resistance F1700	ASTM F2199 modified(70℃) EN16511 modified (70℃)	≤0.15%		
Swelling after submersion	NALFA LF 01-2011	0%		
		Class 4, Heavy Commercial		
IIC & STC	ASTM E492 / ASTM E90	IIC=55 / STC=61 With 1.5mm pad: IIC=64 / STC=61		
Castor Chair Resistance	ISO 4918	Pass		
Fire Rating	ASTM E648/ 662	Class I		
Wear Resistance	EN 13329 method A	Class 34, Heavy Commercial		
F1700	EN 16511	Class 34, Heavy Commercial		
Impact Resistance (Big Ball)	NALFA LF01-2011 EN 16511	Class 4, Heavy Commercial IC3, Class 34, Heavy Commercial		
Impact Resistance (Small Ball)	NALFA LF01-2011	Class 4, Heavy Commercial		
Static coefficient of Friction	ASTM D2047	Dry: 0.38, Wet: 0.9		
Resistance to staining F1700	ASTM F925 NALFA LF01-2011	Pass Class 4, Heavy Commercial		
VOC	FloorScore™	Pass		
Ortho-phthalates	Prop 65	Not Detected / In Compliance		
Lead	CPSIA	None Detected		
Substances of Very High Concern (SVHC)		Not Detected		