

Specifications

Construction: High Density Fiberboard

Edge Type: Pressed Edge/V-Groove

Thickness: 12.3mm

Nominal Length: 48"

Nominal Width: 6-1/2" or 5-5/8"

Coverage per Carton: 18.96/21.7/21.97 ft²

Pieces per Carton: 10

Weight per Carton: 40/46/47 lbs.

Installation Method: Floating

Recommended Usage: Residential &
Light Commercial

Underlayment Required: Yes



This product is protected by a 50 year residential/5 year commercial warranty



Abrasion Class 4 Rating works well in all areas of the home and can withstand moderate commercial traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board. Formaldehyde is less than 0.05%

Our Triple Moisture Collection has been created with the liveliest of homes in mind. Each plank has special wax infused edges that provide outstanding protection against splashes and spills. The contemporary color palette makes the Triple Moisture Collection a great fit in any interior.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


Recommended Underlayment



2mm or
3mm Blue



2mm or
3mm Silver



EVA



Rubber



1/4 Cork



1/2 Cork



NEW VersaPRO Evp 1mm or
NEW VersaPRO Plus Evp 1.5mm
Multi-Purpose Premium Underlayment

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding