

## Specifications

Construction: High Density

Fiberboard

Edge Type: V-Groove

Thickness: 12.3mm

Nominal Length: 48"

Nominal Width: 5"

Coverage per Carton: 19.73 ft<sup>2</sup>

Pieces per Carton: 12

Weight per Carton: 39 lbs.

Installation Method: Floating

Recommended Usage: Residential

Underlayment Required: Yes



This product is protected by a 25 year residential warranty



Abrasion Class 3 Rating works well in all areas of the home and can withstand normal household traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board.

This collection provides a unique variety of styles and colors making it one of our most popular lines.

## Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


## Recommended Underlayment



2mm or 3mm Blue



2mm or 3mm Silver



EVA




Rubber



¼ Cork



½ Cork



NEW VersaPRO Evp 1mm or  
NEW VersaPRO Plus Evp 1.5mm  
Multi-Purpose Premium Underlayment

## Accessories

### MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding