

## Specifications

Construction: High Density  
Fiberboard  
Edge Type: V-Groove  
Thickness: 12.3mm  
Nominal Length: 48"  
Nominal Width: 6-1/2"  
Coverage per Carton: 17.33 ft<sup>2</sup>  
Pieces per Carton: 8  
Weight per Carton: 40 lbs.  
Installation Method: Floating  
Recommended Usage: Residential  
Underlayment Required: Yes



This product is protected by a 25 year residential warranty



Abrasion Class 3 Rating works well in all areas of the home and can withstand normal household traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board. Formaldehyde is less than 0.05%

The subtle distressed textures found in the Exotic Collection perfectly complement any décor.

## Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


## Recommended Underlayment



2mm or  
3mm Blue



2mm or  
3mm Silver



EVA



Rubber



¼ Cork



½ Cork



NEW VersaPRO Evp 1mm or  
NEW VersaPRO Plus Evp 1.5mm  
Multi-Purpose Premium Underlayment

## Accessories

### MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding