

Specifications

Construction: High Density Fiberboard

Edge Type: Pressed Edge

Thickness: 12.3mm

Length: 48"

Width: 6-1/2"

Coverage per Carton: 21.57 ft²

Pieces per Carton: 10

Weight per Carton: 40 lbs.

Installation Method: Floating

Recommended Usage: Residential

Underlayment Required: Yes



This product is protected by a 25 year residential warranty



Abrasion Class 3 Rating works well in all areas of the home and can withstand normal household traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board. Formaldehyde is less than 0.05%

This laminate floor looks and feels like the real thing. The stunning grain patterns and slight shine will add a gorgeous glow to your home.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


Recommended Underlayment



2mm or 3mm Blue




2mm or 3mm Silver



EVA



XPE



Felt



Rubber



1/4 Cork



1/2 Cork

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding